# JN135 Men's Softshell Jacket







## Trendy softshell jacket

Functional 3-layer-fabric with TPU membrane

Wind-proof, breathable and water-proof (5,000 mm water column)

Non-taped seams

Inside made of micro fleece, mesh lining at the front

2 zipped side pockets

Elastic drawstring with stoppers on waist

Zip in front lining for embroideries

JN135: 1 vertical breast pocket with zip

JN137: Slightly waisted

JN135K: Fashionable, reflective piping at the front, back and on the

sleeves

Fabric: Outer fabric (330 g/m²): 95%

polyester, 5% elastane

Country of origin: China

**Customs tariff number** 62019300

### Care instructions



#### Partner article






#### Available colours

	S	М	L	XL	XXL	3XL	4XL	5XL
Weight in g	694g	753g	804g	832g	855g	984g	1001g	1022g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/10	1/10	1/10	1/10	1/10	1/10	1/10	1/10
measurement s in cm	S	M	L	XL	XXL	3XL	4XL	5XL
1/2 chest:	54,00 cm	57,00 cm	61,00 cm	65,00 cm	69,00 cm	73,00 cm	78,00 cm	84,00 cm
1/2 bottom width:	52,00 cm	55,00 cm	59,00 cm	63,00 cm	67,00 cm	71,00 cm	76,00 cm	82,00 cm
front length from shoulder:	67,00 cm	68,00 cm	69,00 cm	70,00 cm	73,00 cm	78,00 cm	80,00 cm	82,00 cm
length back from shoulder:	75,00 cm	76,00 cm	77,00 cm	78,00 cm	80,00 cm	84,00 cm	86,00 cm	88,00 cm
sleevelength incl. shoulder:	78,00 cm	80,00 cm	82,00 cm	84,00 cm	86,00 cm	89,00 cm	89,00 cm	90,00 cm

## Available colours













### Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.

## Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.

## Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 22.06.2020 - 13:52:50