James & Nicholson
JN135K Softshell Jacket Junior

Trendy softshell jacket

Functional 3-layer-fabric with TPU membrane
Wind-proof, breathable and water-proof (5,000 mm water column)
Non-taped seams
Inside made of micro fleece, mesh lining at the front
2 zipped side pockets
Elastic drawstring with stoppers on waist
Zip in front lining for embroideries
JN135: 1 vertical breast pocket with zip
JN137: Slightly waisted
JN135K: Fashionable, reflective piping at the front, back and on the sleeves

XS: 98/104 | S: 110/116 | M: 122/128 | L: 134/140 | XL: 146/152 | XXL: 158/164

Fabric:	Outer fabric (330 g/m²): 95% polyester, 5% elastane
Country of origin:	China
Customs tariff number	62029300

Care instructions

Partner article

Ladies' Softshell Jacket Art-Nr.: **JN137**

Men's Softshell Jacket Art-Nr.: **JN135**

Available colours

	M	L	XL	XXL
Weight in g	457g	505g	525g	587g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/30	1/30	1/30	1/30
measurements in cm	M	L	XL	XXL
Size:	128,00	140,00	152,00	164,00
1/2 chest:	43,00 cm	46,00 cm	49,00 cm	52,00 cm
1/2 bottom width:	42,00 cm	45,00 cm	48,00 cm	51,00 cm
front length from shoulder:	52,00 cm	56,00 cm	60,00 cm	64,00 cm
length back from shoulder:	55,00 cm	59,00 cm	63,00 cm	69,00 cm
sleeve length:	44,00 cm	49,00 cm	54,00 cm	58,00 cm

Available colours

- aqua (2925C)
- carbon (433U)
- olive (5743U)
- black (blackC)
- navy (296C)
- pop-orange (1595C)
- brown (476C)
- off-white (off-white)
- red (187C)

Features

Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.

Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.

Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.